



Emergency Power Pack for Fluorescent Lamp



PP40WFCB

Input Voltage	:	230V +/- 10%, 50/60Hz
Mode of Operation	:	Maintained / Non-maintained
Lamp Used	:	Fluorescent Tube 18 watt or 36 watt
Rated Duration	:	3 hours
Battery Type	:	Maintenance free high temperature Nickel Metal Hydride (Ni-MH) battery 4.8V to 7.2V, 4.0 AH
Charger	:	Solid State Electronic Automatic
Charging Monitor	:	Red LED 5mm diameter
Operating Temperature	:	ta 40 °C
Safety Feature	:	Low voltage cut-off to prevent over-discharge of the battery
Fitting Construction	:	Electro galvanised steel sheet with epoxy powder coating
Product Dimension	:	Power Pack : Length 215 X Width 40 X Height 35 mm
Weight	:	0.43kg (Power Pack module only)
Compliance	:	Malaysia Standards MS 619
Warranty	:	1 Year

Note : Due to continuous development and improvement, our company reserve the right to change specification without notice



Quality Assured By Full SIRIM Licence
in Malaysia since 1992

- Approved by Director General of Fire Service in Malaysia
- Approved by Standard & Industrial Research Institute of Malaysia (SIRIM)
- Approved by Chief Electrical Inspector of Malaysia
- Complies fully with uniform Building By-Law Regulations in Malaysia