



Box Up LED Emergency Exit Light



TR 112LD-EA (double side with arrow)

Input Voltage	: 230V +/- 10%, 50/60Hz
Mode of Operation	: Maintained
Lamp Used	: LED Super Bright High Quality
Rated Duration	: 3 hours
Power Consumption	: 4.2VA
Battery Type	: Maintenance free high temperature Nickel Cadmium (Ni-CD) battery 3.6 V x 1.0 AH
Charger	: Solid State Electronic Automatic
Charging Monitor	: Red LED 5mm diameter
Test Facility	: Micro Switch for independent testing
Operating Temperature	: ta 40 °C
Safety Feature	: Low voltage cut-off to prevent over-discharge of the battery
Fitting Construction	: ABS Engineering Plastic
Product Dimension	: Length 378 X Width 43 X Height 160 mm
Weight	: 1.27kg
Mounting	: Wall, ceiling or pendant mounting
Compliance	: Malaysia Standards MS 983
Warranty	: 5 Years

Note : Due to continuous development and improvement, our company reserve the right to change specification without notice



Quality Assured By Full SIRIM Licence
in Malaysia since 1992

- Approved by Director General of Fire Service in Malaysia
- Approved by Standard & Industrial Research Institute of Malaysia (SIRIM)
- Approved by Chief Electrical Inspector of Malaysia
- Complies fully with uniform Building By-Law Regulations in Malaysia