



Box Up - Keluar Sign



	TR 402 I	TR 403 I	TR 403 F
Power Consumption	: 22.5VA	: 22.5VA	: 39VA
Lamp - Mains "On"	: 2 x 15 watt, 240V Pygmy	: 2 x 15 watt, 240V Pygmy	: Fluorescent tube 1 x 8 watt
Lamp - Mains "Off"	: 2 x 2.5V, 0.4A Bulbs	: 3 x 3.8V, 0.4A Bulbs	: Fluorescent tube 1 x 8 watt
Battery Type	: 4x 1.6AH Ni-MH battery	: 3 x 4AH Ni-MH battery	: 5 x 1.3AH Ni-MH battery
Weight	: 2.2kg	: 2.3kg	: 2.4kg
Product Dimension	: Length 590 mm X Width 58 mm X Height 200 mm		
Input Voltage	: 230V +/- 10%, 50/60Hz		
Rated Duration (hours)	: 3 Hours		
Mode of Operation	: Sustained		
Charger	: Solid State Electronic Automatic		
Charging Monitor	: Red LED 5mm diameter		
Test Facility	: Micro Switch for independent testing		
Operating Temperature	: ta 40 °C		
Safety Feature	: Low voltage cut-off to prevent over-discharge of the battery Incoming AC fuse and Battery DC fuse		
Fitting Construction	: Aluminum casing finish in epoxy powder coating Using "clip-on" design for easy installation		
Diffuser	: Cast Acrylic Sheet		
Mounting	: Wall or ceiling mounting		
Compliance	: Malaysia Standards MS 983		
Warranty	: 1 Year		

Other available designs



KELUAR (Single Sided)
TR 402I (KL)
TR 403I (KL)
TR 403F (KL)



KELUAR (Single Sided)
TR 402I (KR)
TR 403I (KR)
TR 403F (KR)



KELUAR (Double Sided)
TR 402I/D
TR 403I/D
TR 403F/D



KELUAR (R.MAN) (Double Sided)
TR 402I/D (KM)
TR 403I/D (KM)
TR 403F/D (KM)

Note: Due to continuous development and improvement, our company reserve the right to change specification without notice



Quality Assured By Full SIRIM Licence
in Malaysia since 1992

- Approved by Director General of Fire Service in Malaysia
- Approved by Standard & Industrial Research Institute of Malaysia (SIRIM)
- Approved by Chief Electrical Inspector of Malaysia
- Complies fully with uniform Building By-Law Regulations in Malaysia